

Specifications:

Model	DS-6601HFHI(L)	
Video/Audio input	Video compression	H.264
	HD-SDI video input	1-ch, HD-SDI (800mVp-p, 75Ω) 1920×1080P/25Hz, 1920×1080P/30Hz, 1920×1080I/50Hz, 1920×1080I/60Hz, 1920×720P/25Hz, 1280×720P/30Hz, 1920×720P/50Hz, 1280×720P/60Hz
	FC video input	Resolution: 1920×1080P/25Hz, 1280×720P/25Hz, 1600×1200P/25Hz
	HDMI video input	1-ch, Resolution: 1600×1200P/60Hz, 1280×720P/60Hz, 1280×1024P/60Hz, 1024×768P/60Hz
	VGA video input	1-ch, Resolution: 1600×1200P/60Hz, 1920×1080P/60Hz, 1920×1080P/50Hz, 1280×720P/60Hz, 1280×1024P/60Hz, 1024×768P/60Hz, 640×480P/60Hz, 800×600P/60Hz, 1440×900P/60Hz, 1366×768P/60Hz, 1600×900 P/60Hz, 1024×768P/75Hz, 1280×1024 P/75Hz.
	YPbPr video input	1-ch, Resolution: 1920×1080I/60Hz, 1920×1080I/50Hz, 1920×1080P/25Hz, 1920×1080P/30Hz, 1280×720P/60Hz, 1280×720P/50Hz
	Audio compression	G.711
	Audio input	1-ch, RCA (2.0 Vp-p, 1 kΩ)
	Two-way audio	1-ch, RCA (2.0 Vp-p, 1 kΩ)
Video/Audio output	Audio output	1-ch, RCA (Linear, 1 kΩ)
	Video loop output (for DS-6601HFHI(L))	1-ch, HD-SDI interface
	Encoding resolution	1920×1080/1600×1200/1280×1024/1280×720/1024×768/704×576/ 352×288 (depending on the type of video input interface connected)
	Frame rate	1/16~25/30/50/60 fps
	Video bit rate	32 Kbps ~ 16 Mbps
	Audio bit rate	64 Kbps
	Dual stream	Support
	Stream type	Video, Video & Audio
Network Protocols	Protocols Supported	TCP/IP, UDP, IPv4, IPv6; HTTP, RTP, RTSP, NFS, ISCSI, DHCP, NTP, SMTP, SNMPv1, SNMPv2c, SNMPv3, UPNP, SADP, PPPoE, DNS, FTP; IP Server, DynDNS, PeanutHull, HiDDNS, NO-IP; PSIA, HIKCGL, ONVIF.
Network disk	Network Disk	8 network disks (NAS/IP SAN)
	Capacity	Up to 2TB for each disk
External interface	Network interface	1 10 M / 100 M /1000 Mbps Ethernet interface
	Serial interface	1 RS-485, 1 RS-232
	Alarm in	2
	Alarm out	1
Others	Power supply	12 VDC
	Power Consumption	≤ 13W
	Working temperature	-10 °C ~ +55 °C
	Working humidity	10% ~ 90%
	Dimensions (W × D × H)	200 × 123 × 39 mm
	Weight	≤ 1.5 kg