

Specifications

Model		DS-7604NI-K1	DS-7608NI-K1	DS-7616NI-K1	
Video/ Audio input	IP video input	4-ch	8-ch	16-ch	
	Incoming bandwidth	40 Mbps	60 Mbps	80 Mbps	
	Outgoing bandwidth	80 Mbps			
Video/ Audio output	HDMI/VGA output resolution	HDMI: 4K (3840 × 2160)/30Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz			
		VGA: 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz			
Decoding	Audio output	1-ch, RCA (Linear, 1 K Ω)			
	Decoding format	H.265/H.264/H.264+			
	Recording resolution	8MP/6MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF			
	Synchronous playback	4-ch	8-ch	16-ch	
	Capability	2-ch @ 4 MP (30fps)			
	Network management	Network protocols	TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS		
	Hard disk	SATA	1 SATA interface for 1HDD		
Capacity		Up to 6TB capacity for each disk			
External interface	Two-way audio	1-ch, RCA (2.0 Vp-p, 1k Ω)			
	Network interface	1 RJ-45 10 M/100 Mbps self-adaptive Ethernet interface			
	USB interface	2 × USB 2.0			
	Power supply	12 VDC			
General	Consumption (without hard disk)	≤ 10 W			
	Working temperature	-10 to +55° C (14 to 131° F)			
	Working humidity	10 to 90 %			
	Chassis	260 mm chassis			
	Dimensions (W × D × H)	260 × 225 × 48 mm (10.2" × 8.9" × 1.9")			
	Weight (without hard disk)	≤ 1 kg (2.2 lb)			