

Specifications

| Camera | |
|----------------------|---|
| Image Sensor | 1 MP CMOS image sensor |
| Signal System | PAL/NTSC |
| Effective Pixels | 1296(H) × 732(V) |
| Min. Illumination | 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR |
| Shutter Time | 1/25 (1/30)s to 1/50,000 s |
| Lens | 2.8 - 12 mm @ F1.4 |
| | Angle of view: 71.78° - 23.42 ° |
| Lens Mount | φ14 |
| Day & Night | ICR |
| Angle Adjustment | Pan: 0° to 360°, Tilt: 0° to 90°, Rotation: 0° to 360° |
| Synchronization | Internal synchronization |
| Video Frame Rate | 720p@25fps/720p@30fps |
| HD Video Output | 1 analog HD output |
| S/N Ratio | >62dB |
| General | |
| Operating Conditions | -40 °C to 60 °C (-40 °F to 140 °F), Humidity 90% or less (non-condensing) |
| Power Supply | 12 VDC ± 15% |
| Power Consumption | Max. 4 W |
| Protection Level | IP66 |
| IR Range | Up to 40 m |
| Dimensions | 92mm×84.8mm×269.6mm (3.62"×3.34"×3.34") |
| Weight | Approx. 900g (1.98lb) |

Order Model

DS-2CE16COT-VFIR3F