

Specification

Camera Module		2MP 36× Network Positioning System	
Image Sensor	1/1.8" progressive scan CMOS		
Min. Illumination	Color: 0.002 Lux @(F1.5, AGC ON) B/W: 0.0002 Lux @(F1.5, AGC ON)		
White Balance	Auto/Manual/ATW (Auto-tracing White Balance)/ Indoor/Outdoor/Fluorescent lamp/Sodium lamp		
AGC	Auto/Manual		
Shutter Time	1/1 s to 1/30,000 s		
Day & Night	IR Cut Filter		
Digital Zoom	16×		
Privacy Mask	8 programmable privacy masks		
Focus Mode	Auto/Semi-automatic/Manual		
WDR	Digital WDR		
Lens			
Focal Length	5.7 mm to 205 mm, 36× Optical		
Zoom Speed	Approx. 4.4 s (optical lens, wide-tele)		
FOV	Horizontal field of view: 59.8° to 2.0° (wide-tele) Vertical field of view: 33.6° to 1.1° (wide-tele) Diagonal field of view: 68.6° to 2.3° (wide-tele)		
Working Distance	10 mm to 1500 mm (wide-tele)		
Aperture Range	F1.5 to F4.5		
PTZ			
Movement Range (Pan)	360° endless		
Pan Speed	Configurable, from 0.1°/s to 150°/s, Preset Speed: 150°/s		
Movement Range (Tilt)	From -10° to 90° (Auto Flip)		
Tilt Speed	Configurable, from 0.1°/s to 100°/s, Preset Speed: 100°/s		
Proportional Zoom	Support		
Presets	300		
Patrol Scan	8 patrols, up to 32 presets for each patrol		
Pattern Scan	4 pattern scans, record time over 10 minutes for each scan		
Power-off Memory	Support		
Park Action	Preset/Pattern Scan/Patrol Scan/Auto Scan/Tilt Scan/Random Scan/Frame Scan/Panorama Scan		
PTZ Position Display	ON/OFF		
Preset Freezing	Support		
Scheduled Task	Preset/Pattern Scan/Patrol Scan/Auto Scan/Tilt Scan/Random Scan/Frame Scan/Panorama Scan/Dome Reboot/Dome Adjust/Aux Output		
Compression Standard			
Video Compression	Main Stream: H.265+/H.265/H.264+/H.264 Sub-Stream: H.265/H.264/MJPEG Third Stream: H.265/H.264/MJPEG		
H.264 Type	Baseline Profile/Main Profile/High Profile		
H.264+	Support		
H.265 Type	Main Profile		
H.265+	Support		
Video Bitrate	256 kbps to 16384 kbps		
Audio Compression	G.711alaw/G.711ulaw/G.722.1/G.726/MP2L2/PCM		
Audio Bitrate	64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-160Kbps(MP2L2)		

Smart Feature	
Smart Detection	Intrusion Detection, Line Crossing Detection, Audio Exception Detection
ROI encoding	Main stream, sub-stream and third stream respectively support two fixed areas.
Smart Record	ANR (Automatic Network Replenishment), Dual-VCA
Image	
Max. Resolution	1920 × 1080
Main Stream	50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720) 50fps (1920 × 1080, 1280 × 960, 1280 × 720) 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720) 60fps (1920 × 1080, 1280 × 960, 1280 × 720)
Sub-Stream	50Hz: 25fps (704 × 576, 640 × 480, 352 × 288) 60Hz: 30fps (704 × 480, 640 × 480, 352 × 240)
Third Stream	50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 576, 640 × 480, 352 × 288) 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 480, 640 × 480, 352 × 240)
Image Enhancement	HLC/BLC/3D DNR/Defog/EIS/Regional Exposure/Regional Focus
SVC	Support
Network	
Network Storage	Built-in memory card slot, support Micro SD/SDHC/SDXC, up to 256 GB; NAS (NPS, SMB/ CIFS), ANR
Alarm Linkage	Alarm actions, such as Preset, Patrol Scan, Pattern Scan, Memory Card Video Record, Trigger Recording, Notify Surveillance Center, Upload to FTP/Memory Card/NAS, Send Email, etc.
Protocols	IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, DHCP, PPPoE, Bonjour
API	Open-ended, support ONVIF, PSIA and CGI, support HIKVISION SDK and Third-Party Management Platform
Simultaneous Live View	Up to 20 channels
User/Host	Up to 32 users. 3 levels: Administrator, Operator and User
Security Measures	User authentication (ID and PW), Host authentication (MAC address); HTTPS encryption; IEEE 802.1x port-based network access control; IP address filtering
Client	iVMS-4200, iVMS-5200
Web Browser	IE 8+, Firefox 30+, Safari 8.0+ web browser
Interface	
Audio	1-ch audio input/1-ch audio output
Network Interface	1 RJ45 10 M/100 M Ethernet Interface
Alarm	2-ch alarm input/1-ch alarm output
RS-485	Half duplex, HIKVISION, Pelco-P, Pelco-D, self-adaptive
BNC	1.0 V [p-p]/75 Ω, NTSC (or PAL) composite, BNC
General	
Power	24 VAC (Max. 45 W)
Working Environment	Temperature: Outdoor: -40°C to 70°C (-40°F to 158°F) Humidity: ≤ 90%
Protection Level	IP66 Standard; TVS 6000V Lightning Protection, Surge Protection and Voltage Transient Protection
Material	Aluminum alloy ADC12
Dimensions	Φ181 mm × 396 mm × 377.5 mm (Φ 7.13" × 15.59" × 14.86")
Weight	Approx. 7.6 kg (16.76 lb)