

## **Specifications**

	Model	DS-2TS03-35UM/W
Parameter		Handheld Observational Thermal Monocular
Thermal Module	Image sensor	Uncooled Focal Plane Arrays
	Max. Resolution	$384 \times 288$
	Response waveband	8μm to 14μm
	NETD	< 40mk (@25°C,F#=1.0)
	Lens (focal length)	35mm, Manual Focus
	MRAD	0.49
	Field of View	$10.66^{\circ} \times 8^{\circ}$
	Fnumber	1.0
Image Display	Monitor	0.39-inch, OLED, 1024×768
	Palettes	Black hot
		White hot
		Red hot
System	Hot Track	Support
	WIFI	Support
	Storage	Built-in memory module (16GB)
	Digital Zoom	2×
	Capture Snapshot	Support
	Record Video	Support on-board video / image recording
	GPS	Support
Power Supply	Battery Type	Lithium Battery
	Battery Operating Time	Up to five hours continuous running (with GPS function and Wi-Fi
		hot spot function off)
	Battery Capacity Display	Support
General	Power	5V DC/2A, 2W
	Working Temperature	-30 °C to 55 °C (-22 °F to 131 °F)
	Protection level	IP67
	Drop Test Height	2 m (6.56 feet)
	Dimension (L x W x H)	202 mm × 74 mm × 66 mm (7.95 " × 2.91 " × 2.60 ")
	Weight	500 g (1.1 lb)