

DS-D2046NL-B LCD Display Unit



Model	LCD Display Unit	DS-D2046NL-B
Display	Diagonal Size (inch)	46"
	Backlight	LED Backlight (Direct type)
	Panel	S-PVA
	Resolution	1920×1080
	Color	16.7M
	Visual Angle	Horizontal: 178°, Vertical: 178°
	Response Time	8ms (G to G)
	Contrast	4500:1
	Brightness	500cd/m ²
	Dot Pitch (H×V)	0.53025mm×0.53025mm (0.021"×0.021")
	Color Saturation	92%
	Screen Moving Area (H×V)	1018.08mm×572.67mm (40.08"×22.55")
	Side Frame Size	Physical Seam
Interface	Input Interface	VGA×1, DVI×1, BNC×1, YPbPr×1, HDMI×1
	Output Interface	VGA×1, DVI×1, BNC×2
	Control Interface	RJ45 for RS-232
Power	Power Consumption	111 W
	Power Requirement	90~264VAC, 50/60Hz
Working Environment	Operating Temperature	0 °C ~ 40 °C (32 °F ~ 104 °F)
	Operating Humidity	10%~85% (No Condensation)
	Working Life	≥60,000 Hours
Physical Features	Dimension (W×H×D)	1023.8mm×579mm×132mm (40.31"×22.77"×5.20")
	Frame Width	0.14" (Left/Upper), 0.067" (Right/Lower)