

## Specifications

Model	DS-D40C04-H	
Interfaces	<b>Signal input</b>	1-ch DVI, 1-ch HDMI, 1-ch DP, 1-ch VGA
	<b>Signal output</b>	4ch ports output, 1ch DVI output
	<b>Signal control</b>	Network
Processing Performance	<b>Max. resolution</b>	2048 x 1152@60Hz or 1920 x 1200@60Hz
	<b>Frame frequency</b>	60 Hz
	<b>Refresh rate</b>	3840 Hz
	<b>Processing depth</b>	16 bits
	<b>Grey level</b>	65535 bits
	<b>Color</b>	281.4 trillion
	<b>Brightness control</b>	Automatic/manual
General	<b>Dimensions</b>	482.6 x 250 x 44.5 mm (19 x 9.8 x 1.8 inch)
	<b>Power supply</b>	110 to 240VAC ± 15%
	<b>Average power dissipation</b>	≤ 20W
	<b>Working temperature</b>	-10 to 45 °C (14 to 113 °F)
	<b>Storage temperature</b>	-20 to 60 °C (-4 to 140 °F)
	<b>Working humidity</b>	10 to 90%
	<b>Storage humidity</b>	10 to 90%

**Note:** All specifications mentioned above are subject to the actual product.