

Specifications

| Camera | |
|----------------------|---|
| Image Sensor | 2 MP CMOS image sensor |
| Signal System | PAL/NTSC |
| Effective Pixels | 1920 (H) × 1080 (V) |
| Min. illumination | 0.01 Lux@(F1.2, AGC ON) |
| Shutter Time | PAL: 1/25 s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s |
| Lens | 3.6 mm (6 mm optional) |
| | Field of view: 82° (3.6 mm), 54° (6 mm) |
| Lens Mount | M12 |
| Day & Night | Color |
| Angle Adjustment | Pan: 0° to 360°, tilt: 0° to 90° |
| Synchronization | Internal synchronization |
| Video Frame Rate | 1080p@25fps 1080p@30fps |
| HD Video Output | 1 analog HD output |
| S/N Ratio | > 62 dB |
| General | |
| Operating Conditions | -40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation) |
| Power Supply | 12 V DC ±10% |
| Power Consumption | Max. 1 W (white supplement light off) Max. 3 W (white supplement light on) |
| Protection Level | IP66 |
| White Light Distance | Up to 30 m |
| Dimensions | 194.07 mm × 93.52 mm × 93.87 mm (7.64" × 3.68" × 3.7") |
| Weight | Approx. 450 g (0.99 lb.) |

Order Model

DS-2CE16D0T-WL3