

Model	DS-2CC11A1P(N)-A
Parameter	700 TVL CCD Box Camera
Camera	
Image Sensor	1/3" SONY CCD
Signal System	PAL/NTSC
Effective Pixels	PAL: 976 (H) × 582 (V) NTSC: 976 (H) × 494 (V)
Min. Illumination	Color: 0.001 Lux @ (F1.2, AGC ON) B/W: 0.0001 Lux @ (F1.2, AGC ON)
Shutter speed	PAL: 1/50 s to 1/10,000 s NTSC: 1/60 s to 1/10,000 s
Lens Mount	C/CS mount
Auto Iris	DC drive
Day & Night	IR cut filter with auto switch
Horizontal Resolution	700TVL
Synchronization	Internal/Power synchronization
Video Output	1Vp-p composite output (75 Ω/BNC)
S/N Ratio	More than 62 dB
Menu	
Camera ID	On/Off (52 letters, position adjustable)
D/N Mode	Auto /Day /Night/ EXT1/ EXT2
White Balance	ATW/PUSH/USER1/USER2/ANTI CR/MANUAL/PUSH LOCK
Private Mask	On/Off, maximum 8 zones
Motion Detection	On/Off
Back Light	BLC/HLC/Off
Language	Chinese/ English/ Japanese/ German/ French/ Russian/ Portuguese/ Spanish
Function	SMART IR,ATR, HLC, DNR, Sharpness, Brightness, Contrast, Hue, Gain, Mirror, Defect Pixel
General	
Working Temperature/Humidity	-10 °C - 60 °C (14 °F - 140 °F) Humidity 90% or less (noncondensing)
Power Supply	24 V AC ± 10%, 12 V DC ± 10%
Power Consumption	Max. 2 W (Max. 4 W with IR cut filter on)
Dimensions	68.8 x 56 x 111 mm (2.71" × 2.20" × 4.37")
Weight	400 g (0.88 lbs)