

Specifications

Model		DS-3E0108P-E	DS-3E0109P-E/M	DS-3E0318P-E/M	DS-3E0326P-E/M	
Port	10/100 Mbps RJ45	8	9	16	24	
	10/100/1000 Mbps RJ45	/	/	1		
	1000 Mbps SFP	/	/	1 independent		
	High-priority Port	/	Port 1 - 2	Port 1 - 8		
	Lightning-proof Ranking	/	4 kV			
	Working Mode	/	EXTEND OFF, EXTEND ON	Extend (Port9-16), Priority, Standard, Isolate	Extend (Port17-24), Priority, Standard, Isolate	
Performance	Store-and-forward	Supported				
	MAC Address Table	1 k	4 k			
	MAC Learning	Auto-learning/ Auto-aging				
	Switching Capacity	1.6 Gbps	1.8 Gbps	7.2 Gbps	8.8 Gbps	
PoE Power	PoE standard	IEEE 802.3af, IEEE802.3at				
	PoE Powering Mode	Two pair of wires: pins 1 and 2, and pins 3 and 6	Supports 8-pin power supply			
	PoE Port	1 - 4	1 - 8	1 - 16	1 - 24	
	Maximum Output Port	30 W				
	Maximum Output Total	58 W		135 W	225 W	
Power Input		51 V DC, 1.25 A		100~240 V AC, 50/60 Hz		
Power Consumption		≤63w	≤63w	≤150w	≤250w	
Environment	Operating Environment	Operating Temperature: 0 °C ~ 40 °C Operating Humidity: 10% - 90% RH non-condensing				
	Storage Environment	Storage Temperature: -40 °C ~ 70 °C Storage Humidity: 5% - 90% RH non-condensing				
Transmission Speed		Ethernet: 10 Mbps (Half Duplex) / 20 Mbps (Full Duplex) Fast Ethernet: 100 Mbps (Half Duplex) / 200 Mbps (Full Duplex)		Ethernet: 10 Mbps (Half Duplex) / 20 Mbps (Full Duplex) Fast Ethernet: 100 Mbps (Half Duplex) / 200 Mbps (Full Duplex) Gigabit Ethernet: 2000 Mbps (Full Duplex)		
Transmission Medium		Ethernet: Cat 3 or better UTP/STP Fast Ethernet: Cat 5 or better UTP/STP		Ethernet: Cat 3 or better UTP/STP Fast Ethernet: Cat 5 or better UTP/STP Gigabit Ethernet: Cat 5 or better UTP/STP 1000 Base-SX: MMF (Multimode optical fiber) 1000 Base-LX: MMF (Multimode optical fiber) or SMF (Single Mode Fiber)		
Network Standard		IEEE 802.3, IEEE 802.3u, IEEE 802.3af, IEEE802.3at, IEEE 802.3x		IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3x, IEEE 802.3z		