

Specifications

Model		DS-7204HQHI-SH	DS-7208HQHI-SH	DS-7216HQHI-SH	
Video/Audio input	Video compression	H.264			
	Analog and HDTVI video input	4-ch	8-ch	16-ch	
		BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection			
	Supported camera types	720p25, 720p30, 720p50, 720p60, 1080p25, 1080p30, CVBS			
	IP video input	2-ch			
		Up to 1080p resolution			
	Audio compression	G.711u, G.726, G.711a, G.722			
Audio input	4-ch, RCA (2.0 Vp-p, 1 KΩ)				
Video/Audio output	HDMI/VGA output	1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz			
	Encoding resolution	1080p/720p/VGA/WD1/4CIF/CIF			
	Frame rate	Main stream: 1080p/720p/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N)			
		Sub-stream: WD1/4CIF@12fps; CIF/QCIF/QVGA@25fps (P)/30fps (N)			
	Video bit rate	32 Kbps to 10 Mbps			
	Audio output	1-ch, RCA (Linear, 1 KΩ)			
	Audio bit rate	64 Kbps			
	Dual stream	Support			
	Stream type	Video, Video & Audio			
	Synchronous playback	4-ch	8-ch	16-ch	
Network management	Remote connections	128			
	Network protocols	TCP/IP, PPPoE, DHCP, Hik Cloud P2P, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS			
Hard disk	SATA	1 SATA interface	2 SATA interfaces		
	Capacity	Up to 6 TB capacity for each disk			
External interface	Two-way audio input	1-ch, RCA (2.0 Vp-p, 1 KΩ) (using the 1 st channel of audio input)			
	Network interface	1, 10M/100M/1000M self-adaptive Ethernet interface			
	Serial interface	RS-485 (half-duplex)			
	Alarm in/out	4/1	8/4	16/4	
	USB interface	2 × USB 2.0			
General	Power supply	12 VDC			
	Consumption (without HDD)	≤ 15 W	≤ 30 W	≤ 45 W	
	Working temperature	-10 °C to +55 °C (14 °F to 131 °F)			
	Working humidity	10% to 90%			
	Dimensions (W × D × H)	315 × 242 × 45 mm (12.4 × 9.5 × 1.8 inch)		380 × 290 × 48 mm (15.0 × 11.4 × 1.9 inch)	
		Weight (without HDD)	≤ 1.5 kg (3.3 lb)		≤ 2 kg (4.4 lb)