

Specifications

| Model | | DS-7708NI-K4 | DS-7716NI-K4 | DS-7732NI-K4 |
|----------------------------|---------------------------------|--|--------------|--------------|
| Video/ Audio input | IP video input | 8-ch | 16-ch | 32-ch |
| | Incoming bandwidth | 80 Mbps | 160 Mbps | 256 Mbps |
| | Outgoing bandwidth | 160 Mbps | | |
| Video/ Audio output | HDMI output resolution | 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz | | |
| | VGA output resolution | 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz | | |
| | Audio output | 1-ch, RCA (Linear, 1 KΩ) | | |
| Decoding | Decoding format | H.265/H.265+/H.264+/H.264/MPEG4 | | |
| | Recording resolution | 8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF /2CIF/CIF/QCIF | | |
| | Synchronous playback | 8-ch | 16-ch | 16-ch |
| | Capability | 2-ch @ 8 MP (25fps) / 4-ch @ 4MP (30fps) / 8-ch @ 1080p (30fps) | | |
| Network management | Network protocols | TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS | | |
| Hard disk | SATA | 4 SATA interfaces | | |
| | Capacity | Up to 6TB capacity for each HDD | | |
| External interface | Two-way audio | 1-ch, RCA (2.0 Vp-p, 1kΩ) | | |
| | Network interface | 2 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interfaces | | |
| | Serial interface | 1 RS-485 (half-duplex), 1 RS-232, 1 keyboard (optional) | | |
| | USB interface | Front panel: 2 × USB 2.0; Rear panel: 1 × USB 3.0 | | |
| | Alarm in/out | 16/4 | | |
| General | Power supply | 100 to 240 VAC | | |
| | Power | ≤ 80 W | | |
| | Consumption (without hard disk) | ≤ 20 W | | |
| | Working temperature | -10 to +55°C (14 to 131°F) | | |
| | Working humidity | 10 to 90 % | | |
| | Chassis | 19-inch rack-mounted 1.5U chassis | | |
| | Dimensions (W × D × H) | 445 × 400 × 71 mm (17.5" × 15.7" × 2.8") | | |
| Weight (without hard disk) | ≤ 5 kg (11. lb) | | | |