

Specification

Model		DS-7716NXI-I4/4S	DS-7732NXI-I4/4S
Video/Audio input	IP video input	16-ch	32-ch
	Two-way audio	1-ch, RCA (2.0 Vp-p, 1 k Ω)	
Network	Incoming/Outgoing bandwidth	256 Mbps/200 Mbps	
Video/Audio output	Recording resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF	
	CVBS output (Optional)	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480	
	HDMI/VGA resolution (as main port)	4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz 4K resolution is only available for HDMI.	
	HDMI/VGA resolution (as aux port)	1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	
	Audio output	1-ch, RCA (Linear, 1 KΩ)	
Decoding	Decoding format	H.265/H.265+/H.264/H.264+/MPEG4	
	Synchronous playback	16-ch	
	Capability	12-ch @ 1080p	
Smart analysis	Capability	False alarm filtering for 4-ch behavior (line crossing and intrusion) detection for 2 MP, 3 MP, and 4 MP network camera	
Hard disk	SATA	4 SATA interfaces for four 3.5-inch HDDs	
	Capacity	Up to 8 TB capacity for each HDD	
	eSATA	1 eSATA interface	
External interface	Network interface	2, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface	
	Serial interface	RS-485 (half-duplex), RS-232, Keyboard	
	USB interface	Front panel: 2 × USB 2.0; Rear panel: 1 × USB 3.0	
	Alarm in/out	16/4	
General	Power supply	100 to 240 VAC	
	Power	≤ 80 W	
	Consumption (without HDD)	≤ 30 W	
	Working temperature	-10° C to +55° C (+14° F to +131° F)	
	Working humidity	10 to 90 %	
	Chassis	1.5U chassis	
	Dimensions (W × D × H)	445 × 400 × 71 mm (17.5"× 15.7" × 2.8")	
Weight (without HDD)	≤ 5 kg (11 lb)		