

# DS-7700NI-I4 Series NVR



## Specifications

Model		DS-7716NI-I4	DS-7732NI-I4
Video/Audio input	IP video input	16-ch Up to 12 MP resolution	32-ch
	Two-way audio	1-ch, RCA (2.0 Vp-p, 1kΩ)	
Network	Incoming bandwidth	160 Mbps	256 Mbps
	Outgoing bandwidth	256 Mbps	
	Remote connection	128	
Video/Audio output	Recording resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF /CIF/QCIF	
	HDMI output resolution	4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	
	VGA output resolution	1920 × 1080p/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	
	Audio output	1-ch, RCA (Linear, 1 KΩ)	
Decoding	Decoding format	H.265/H.264/MPEG4	
	Live view / Playback resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF /CIF/QCIF	
	Synchronous playback	16-ch	
	Capability	4-ch @ 4K, or 16-ch @ 1080p	
Hard disk	SATA	4 SATA interfaces for 4HDDs	
	Capacity	Up to 6TB capacity for each HDD	
External interface	Network interface	2 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interfaces	
	Serial interface	1 RS-485 (half-duplex), 1 RS-232	
	USB interface	Front panel: 2 × USB 2.0; Rear panel: 1 × USB 3.0	
	Alarm in/out	16/4	
General	Power supply	100 to 240 VAC	
	Power	≤80 W	
	Consumption (without hard disk)	≤20 W	
	Working temperature	-10 to +55°C (14 to 131°F)	
	Working humidity	10 to 90 %	
	Chassis	19-inch rack-mounted 1.5U chassis	
	Dimensions(W × D × H)	445 × 390 × 70 mm ( 17.5" × 15.3" × 2.8")	
	Weight(without hard disk)	≤ 5 Kg (11 lb)	