

Specification

Model	DS-K1T606M	DS-K1T606MF
Operation system	Linux	
LCD screen	5-inch LCD touch screen; resolution: 480 × 800	
Camera	2 MP; WDR; wide-angle lens	
1:N face recognition duration	≤ 1s/person	
Face recognition accuracy rate	≥ 99%	
Face recognition distance	0.3 m to 1 m	
Face capacity	3200	
Fingerprint capacity	/	5000
Card capacity	5000	
Event capacity	100,000	
Communication mode	10/100 Mbps self-adaptive network interface; Wi-Fi	
Interface	RS-485 × 1, Wiegand × 1, USB × 1, lock × 1, exit button × 1, tamper × 1, alarm input × 2, alarm output × 1, door contact × 1	
Power supply	12 VDC/2 A (centralized power supply)	
Working temperature	-20 °C to 50 °C (-4 °F to 122 °F)	
Working humidity	10% to 90% (no condensing)	
Installing method	Wall mounting (with/without gang box)	
Dimensions	281.5 mm × 113 mm × 45 mm (11.08" × 4.45" × 1.77")	
Application situation	Indoor; outdoor	
Protection Level	IP65	

* Exposing the equipment to direct sun light, low ventilation or heat source such as heater or radiator is forbidden (ignorance can cause fire danger).

* For device with fingerprint module, we suggest that do not install the device outdoors.