

DS-3E0318P-E

16-ports 100Mbps Unmanaged PoE Switch



Specifications

Model	DS-3E0318P-E
Ports	
Network Ports	18
PoE Port	16, 10/100Mbps RJ45 ports
Uplink Port	2, 1000M Combo Port
Standard	
Network Protocol	IEEE802.3,802.3u,802.3x, 802.3af, 802.3at
Performance	
Switching Capacity	7.2Gbps
Max. Forwarding Rate	5.36Mpps
High Priority Ports	Ports 1-8
Forwarding Mode	Store-and-forward
MAC Address Table	4k
Flow Control	IEEE802.3x full duplex
Power Over Ethernet	
PoE Standard	IEEE802.3af, IEEE802.3at
PoE Power Budget	230W
Working Mode	Extend On:250m,10M,CAT 5e
	Extend Off:100m
General	
Power Supply	100-240V AC, 50/60Hz
Power Consumption	≤250W
Surge Protection	4KV
Working Temperature	Temperature: 0°C-40°C
Working Humidity	Humidity: 10%-90% , non-condensing
Storage Temperature	Temperature: -40°C-70°C
Storage Humidity	Humidity: 5%-90% , non-condensing
Weight	3.72kg
Dimension	440mm*285mm*43mm
Accessories	
SFP modules (Optional)	HK-1.25G-20-1550: 1000M SFP module, TX1550nm/RX1310nm, LC, single-mode single-fiber, 20km HK-155M-20-1550: 100M SFP module, TX1550nm/RX1310nm, LC, single-mode single-fiber, 20km