

Specifications

Model	iDS-6716NXI-I/16S(B)	
Human/vehicle analysis	False alarm filtering	Up to 16-ch 2 MP video analysis for human and vehicle recognition to filter false alarm
Video/Audio output	VGA output	N/A
	HDMI output	N/A
	Audio output	1-ch, RCA (Linear, 1 KΩ)
Video/Audio input	IP video input	16-ch
	Incoming/Outgoing bandwidth	320 Mbps/256 Mbps
Decoding	Dncoding format	H.265/H.265+/H.264/H.264+/MPEG4
	Live view/playback resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
	Synchronous playback	16-ch
	Capability	16-ch @ 1080p
Hard disk	Hard disk	1, built-in 2.5-inch 2 TB SATA hard disk
External interface	Two-way audio	1-ch, RCA (Linear, 1 KΩ)
	Network interface	2, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
	Serial interface	RS-232; RS-485
	USB interface	N/A
	Alarm in/out	16/4
General	Power supply	12 VDC
	Total power	40 W
	Consumption (without hard disk)	≤ 30 W
	Working temperature	-10 °C to 55 °C (14 °F to 131 °F)
	Working humidity	10 to 90 %
	Dimensions (W × D × H)	315 × 65 × 240.8 mm (12.4"× 2.6" × 9.5")
	Weight (without hard disk)	≤ 3 kg (6.6 lb)