

## Specification

<b>Model</b>	<b>DS-7316HTHI-K4</b>
<b>Recording</b>	
<b>Video compression</b>	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
<b>Encoding resolution</b>	8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF
<b>Frame rate</b>	Main stream: 8 MP@12 fps/5 MP@20 fps; 3 MP@18fps; 4 MP/1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N)
	Sub-stream: WD1/4CIF/CIF@25fps (P)/30fps (N)
<b>Video bit rate</b>	32 Kbps to 16 Mbps
<b>Dual stream</b>	Support
<b>Stream type</b>	Video, Video & Audio
<b>Audio compression</b>	G.711u
<b>Audio bit rate</b>	64 Kbps
<b>Video and Audio</b>	
<b>IP video input</b>	16-ch (up to 32-ch)
	Up to 8 MP resolution
	Support H.265+/H.265/H.264+/H.264 IP cameras
<b>Analog video input</b>	16-ch
	BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection
<b>HDTVI input</b>	8 MP, 5 MP, 4 MP, 3 MP, 1080p25, 1080p30, 720p25, 720p30, 720p50, 720p60
<b>AHD input</b>	5 MP, 4 MP, 720p25, 720p30, 1080p25, 1080p30
<b>HDCVI input</b>	4 MP, 720p25, 720p30, 1080p25, 1080p30
<b>CVBS input</b>	PAL/NTSC
<b>CVBS output</b>	1-ch, BNC (1.0 Vp-p, 75 Ω)
<b>HDMI1/VGA output</b>	1-ch, 1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
<b>HDMI2 output</b>	1-ch, 4K (3840 × 2160)/30 Hz, 2K (2560 × 1440)/60 Hz, 1920 × 1080/60Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
<b>Audio input</b>	4-ch, RCA (2.0 Vp-p, 1 KΩ)
<b>Audio output</b>	2-ch, RCA (Linear, 1 KΩ)
<b>Two-way audio</b>	1-ch, RCA (2.0 Vp-p, 1 KΩ) (independent)
<b>Synchronous playback</b>	16-ch
<b>Network</b>	
<b>Remote connections</b>	128
<b>Network protocols</b>	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF, SNMP
<b>Network interface</b>	2, RJ45 10M/100M/1000M self-adaptive Ethernet interface
<b>Auxiliary interface</b>	
<b>SATA</b>	4, SATA interface
<b>eSATA</b>	1, eSATA interface
<b>Capacity</b>	Up to 10 TB capacity for each disk
<b>Serial interface</b>	RS-232, RS-485 (full-duplex), Keyboard
<b>Alarm in/out</b>	16/4

<b>USB interface</b>	Front panel: 2 × USB 2.0 Rear panel: 1 × USB 3.0
<b>General</b>	
<b>Power supply</b>	100 to 240 VAC
<b>Consumption (without HDD)</b>	≤ 45 W
<b>Working temperature</b>	-10 °C to 55 °C (14 °F to 131 °F)
<b>Working humidity</b>	10% to 90%
<b>Dimension (W × D × H)</b>	445 × 390 × 70 mm (17.5 × 15.4 × 2.8 inch)
<b>Weight (without HDD)</b>	≤ 6 kg (13.2 lb)