

SPECIFICATION

Model		DS-19A08/16-BN	DS-19A08/16-BNG
Security Control Panel Parameters	Alarm Input	8/16 inputs onboard expandable to 48	
	Alarm Output	4 outputs onboard and expandable to 48 (Capacity:30VDC/1A)	
	Siren Power Supply	12VDC /750mA	
	PSTN	YES	
	Supported Keypads (LCD)	32	
	Tamper-proof Switch	1, Support tamper-proof function	
	Scheduled arm/disarm	8 time segments each day	
	Partitions	8 partitions, including 1 public partition	
	Detector Tamper-proof Alarm	YES	
	SMS Alarm-Report Push	N/A	YES
	Arming/Disarming via SMS Command	N/A	YES
	Key Fobs	32 (Open area 100m)	
	Wireless Network Standard		GPRS
	UIM Card Slot	N/A	1
SMA Antenna Interface		1	
Network Management	Network Application	DNS and DHCP	
External Interface	Network Interface	1 RJ45, 10M/100M Self-adaptive	
	Keypad Interface	1 RS485 Half-duplex	
	Port for accumulator	1 , 12VDC/7Ah	
	Printer Interface	1 RS-232	
Others	Power Supply	AC220V	
	Consumption	≤40W(Load Power≤40W)	
	Working Temperature	-10°C~+55°C	
	Working Humidity	10%~90%	
	Installation Mode	Wall-mounting	
	Dimensions(L x W x H)	370mm×320mm×86mm	
Weight	< 3.5kg		