

Specifications

Model	DS-D5032FC-A	
Backlight	LED Backlight	
Screen Size	31.5 inch	
Pixel Pitch	0.12125 mm (H) × 0.36375 mm (V)	
Max Resolution	1920×1080@60Hz	
Brightness	300 cd/m ²	
Contrast	1000: 1	
Response Time	8 ms	
Color	16.7M	
Active Area (H×V)	698.40 mm x 392.85 mm	
Viewing Angle	Horizontal 178°, vertical 178°	
Interfaces	DVI input	1
	HDMI input	1
	VGA input	1
	BNC(in/out)	In×1, Out×1
	PC Audio(in/out)	In×1, Out×1, 3.5 mm mini-jack
	USB	1
Loudspeaker	2 W x 2, 6Ω	
Power Supply	AC 100 ~ 240 V , 50/60 Hz	
Power Consumption	≤45W	
Standby Power Consumption	≤ 0.5 W	
Working Temperature	0 to 40 ° C (32 to 104 ° F)	
Working Humidity	10 to 85 %	
Storage Temperature	-10 to 55 ° C (-4 to 131 ° F)	
Storage Humidity	5 to 95%	
Color of Casing	Black	
VESA	M4, 100 mm × 100 mm	
Dimensions(W*H*D)	729mm x 433mm x 50mm / 728.8mm x 526mm x 167.2mm(with base)	
Package Dimension (W×H×D)	803mm x 513mm x 197mm	
Gross Weight	9.25Kg	
Net Weight	5.75kg	
Accessories	VGA cable	1
	HDMI cable	1
	Power cord	1
	Remote control	1
	Battery	2
	User manual	1
	Base bracket	1
	Warranty card	1
Bracket	Base bracket	Contain 1
	Wall mounted	Optional DS-DM1940W
*Note	All specifications mentioned above are subject to the actual product	