

Specifications

Model	DS-D5032FL			
Backlight	LED Backlight			
Screen Size	31.5"			
Pixel Pitch	0.36375 mm x 0.36375 mm			
Max Resolution	1920 x 1080			
Brightness	400 cd/m ² (Typical)			
Contrast	3000 : 1			
Response Time	10 ms			
Color	16.7 M			
Active Area	698.40 mm x 392.85 mm			
Viewing Angle	Horizontal 178°, Vertical 178°			
Interfaces	VGA Input	1	RS-232 interface	1
	BNC Input	1	IR Receiver	1 (for remot control)
	BNC Output	1	Audio input	1
	USB 2.0 Interface	1	Audio output	1
	HDMI input	1	VGA Input	1
Power Supply	24 VDC; 100 to 240 VAC, 50/60Hz			
Power Consumption	≤ 60 W			
Standby Power Consumption	< 0.5 W(Standby)			
Loudspeaker	3W x 2			
Working Temperature	0 °C ~ 40 °C(32°F ~ 104°F)			
Working Humidity	10% ~ 90% (No Condensation)			
Storage Temperature	-20°C ~ 60°C(-4°F ~ 140°F)			
Storage Humidity	10%~90% (No Condensation)			
Color of Casing	Black			
VESA	4-M6 200 mm * 200 mm			
Dimensions(W*H*D)	737.4 mm × 452.5 mm × 70.65 mm			
Packing Dimensions(W*H*D)	881 mm x 630 mm x 205 mm			
Gross Weight	19 kg			
Net Weight	12 kg			
Accessories	Power cord	1		
	User manual	1		
	Warranty card	1		
	Remote control	1		
	Battery	2		
Bracket	Pedestal	Optional	DS-DM3201B	
	Wall mounted	Optional	DS-DM1940W	
*Note	All specifications mentioned above are subject to the actual product			