

Specifications

Model	DS-D5032FL-C	
LCD Screen	Backlight	LED Backlight
	Dimension	31.5 inch
	Dot pitch	0.3637 mm × 0.3637 mm
	Max. resolution	1920 × 1080p
	Optimal working resolution	1920 × 1080@60Hz
	Brightness	400 cd/m ²
	Contrast	3000: 1
	Response time	6.5 ms
	Color	16.7M
	Active Area	698.4 × 392.85 mm
	Viewing Angle	Horizontal 178°, vertical 178°
Interfaces	HDMI input	1
	VGA Input	1
	LAN Interface	1
	USB 2.0 Interface	1
	Audio input	1
	Audio output	1
	IR Receiver	1 (for remote control)
General	Casing Material	Metal
	Color of Casing	Black
	Wall-mounting Hole	200 × 200 mm
	Wall-mounting Screw	M6
	Power Supply	24 VDC; 100 to 240 VAC, 50/60Hz
	Power Consumption	≤ 65 W
	Standby Power Consumption	≤ 0.5 W
	Working Temperature	0 to 40 °C (0 to 104 °F)
	Working Humidity	10 to 90 %
	Storage Temperature	-20 to 60 °C (-68 to 140 °F)
	Storage Humidity	10 to 90%
	Dimensions (without base)	737.4 × 508 × 74.9 mm (29" × 20" × 2.9")
	Packing Dimensions	888 × 210 × 680 mm (35.0 × 8.3" × 26.8")
Gross Weight	22 kg (48.5 lb)	
Net Weight	18 kg (39.7 lb)	

Note: All specifications mentioned above are subject to change without prior notice.

Model	DS-2CD2125FWD-IM	
Camera	Image Sensor	1/2.8" Progressive Scan CMOS
	Min. Illumination	Color: 0.005 lux @(F1.2, AGC ON), 0 lux with IR on
	Shutter Speed	1/3 s to 1/100,000 s
	Slow Shutter	Support
	Lens	2.8 mm, horizontal field of view: 108°
	Lens Mount	M12
	Iris	F1.6
	Day & Night	IR cut filter
	DNR	3D DNR
	Wide Dynamic Range	120dB
Compression Standard	Video Compression	Main stream: H.265/H.264 Sub stream: H.265/H.264/MJPEG Third stream: H.265/H.264
	H.264 Type	Main Profile/High Profile
	H.264+	Support
	H.265 Type	Main Profile
	H.265+	Support
	Video Bit Rate	32 Kbps to 16 Mbps
Image	Max. Resolution	1920 × 1080
	Main Stream	50Hz: 25fps (1920 × 1080, 1280 × 960, 1280×720) 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280×720)
	Sub Stream	50Hz: 25fps (640 × 360, 352 × 288) 60Hz: 30fps (640 × 360, 352 × 240)
	Third Stream	50Hz: 25fps (1920 × 1080) 60Hz: 30fps (1920 × 1080)
	Image Enhancement	BLC/3D DNR
	Image Settings	Support rotate mode. Brightness, contrast, saturation, and sharpness are adjustable via web browser and client software
	ROI (Region of Interest)	Support 1 fixed region for each stream, and face dynamic tracking
	Target Cropping	Support
	Day/Night Switch	Auto/Scheduled
Network	Alarm Trigger	Motion Detection, Tampering Alarm, Network Disconnected, IP Address Conflict, Illegal Login, HDD full, HDD error
	Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6
	Standard	ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI
	General Function	Anti-Flicker, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark, IP Address Filter
	On-board Storage	Built-in microSD/SDHC/SDXC slot, up to 128 G

Note: All specifications mentioned above are subject to change without prior notice.