

# Specifications

Model	DS-D5050UC	
LCD Screen	Backlight	LED Backlight
	Dimension	50 inch
	Optimal working resolution	3840 × 2160@60Hz
	Brightness	300 cd/m <sup>2</sup>
	Contrast	4000: 1
	Response time	8ms
	Color	16.7M
	Active Area	1095.84 × 616.41 mm
	Viewing Angle	Horizontal 178°, vertical 178°
Interfaces	LAN	1
	VGA input	1
	HDMI input	1
	AV input	1 (CVBS IN, L Audio input, R Audio input)
	USB 2.0	1
	USB 3.0	1
	SPDIF output	1
General	Casing Material	Plastic
	Color of Casing	Black
	Wall-mounting Hole	400 × 200 mm
	Wall-mounting Screw	M6
	Speakers	2*8W
	Power Supply	100 to 240 VAC, 50/60Hz
	Power Consumption	≤ 117W
	Standby Power Consumption	≤ 0.5 W
	Working Temperature	0 to 40 °C (0 to 104 °F)
	Working Humidity	10 to 90 %
	Storage Temperature	-20 to 60 °C (-68 to 140 °F)
	Storage Humidity	5 to 95%
	Dimensions	1123.6 × 649.3 × 77 mm
	Packing Dimensions	1280 × 845 × 203 mm
Gross Weight	12.35 kg	
Net Weight	12.00 kg	
Accessories	Specification*1, Power cord*1, HDMI cable*1, Remote control*1	

**Note:** All specifications mentioned above are subject to the actual product.