

## Specifications

<b>Model</b>		<b>DS-KB2421-IM</b>
<b>Video parameters</b>	<b>Camera</b>	1/4" CMOS
	<b>Resolution</b>	720 × 576
	<b>Video frame rate</b>	PAL: 25 fps
<b>Audio parameters</b>	<b>Audio input</b>	Built-in Omnidirectional Microphone
	<b>Audio output</b>	Built-in Loudspeaker
	<b>Audio quality</b>	Noise Suppression
<b>Light supplement</b>	<b>Light supplement mode</b>	Photosensitive IR Supplement, IR Range: 2 Meters
<b>Device interfaces</b>	<b>Four-wire interface</b>	1 Four-Wire Interface (1-ch Video Input, 1-ch Audio Input/Output, 1-ch Power Supply, 1-ch Grounding)
	<b>I/O output</b>	1 Relay Output
<b>General</b>	<b>Material</b>	Zinc Alloy
	<b>Power consumption</b>	Max. 5W
	<b>Working temperature</b>	-30° C to +70° C (-22° F to 158° F)
	<b>Working humidity</b>	10% to 90%
	<b>Dimensions (L × W × H)</b>	145 mm × 49.2 mm × 26.45 mm (5.7" × 1.9" × 1.0")