

Specifications

Model	DS-KD8002-VM	
System parameters	Processor	High-Performance Embedded SOC Processor
	Operation system	Embedded Linux Operation System
Video parameters	Camera	CMOS Low Illumination 1.3 MP HD Colorful Camera
	Video compression standard	H.264
	Resolution	1280 × 720
	Video frame rate	PAL: 25 fps, NTSC: 30 fps
Display parameters	Display screen	3.5-Inch Colorful TFT LCD
	Display resolution	480 × 320
	Operation method	Physical Keypad
	Operation interface	LCD Display, Easy Menu
Audio parameters	Audio input	Built-in Omnidirectional Microphone
	Audio output	Built-in Loudspeaker
	Audio compression standard	G.711 U
	Audio compression rate	64 Kbps
	Audio quality	Noise Suppression and Echo Cancellation
Access control parameters	Internal card reader	Built-in IC Card Reader
	External card reader	Wiegand 26, Wiegand 34, or RS-485 IC Reader
	Door magnetic detection	Detects Door Magnetic Status
Light supplement	Light supplement mode	Visible Light Supplement
Network parameters	Ethernet	10/100/1000 Mbps Self-Adaptive Ethernet
	Network protocol	TCP/IP, RTSP
Alarm parameters	Alarm input	Door Magnetic Alarm, Tampering Alarm
Device interfaces	Network interface	1 RJ-45 10/100/1000 Mbps Self-Adaptive Ethernet Interface
	RS-485	1 RS-485 Half-Duplex Port
	I/O input	8
	I/O output	4
	Wiegand	1 Wiegand Port for Accessing Wiegand IC Card Reader
	USB	1 USB 2.0, Supporting U-Disk
General	Material	Aluminum Alloy
	Power supply	12 VDC
	Power consumption	≤15 W
	Working temperature	-40° C to +60° C (-40° F to 140° F)
	Working humidity	10% to 90%
	IP protection level	IP65
	Dimensions (L × W × H)	418 mm × 145 mm × 61 mm (16.5" × 5.7" × 2.4")
Certification	FCC, IC, CE, C-TICK, ROHS, REACH, WEEE	