

Specifications

Model		DS-KV8102-IM	DS-KV8202-IM	DS-KV8402-IM
System parameters	Processor	High-Performance Embedded SOC Processor		
	Operation system	Embedded Linux Operation System		
Video parameters	Camera	CMOS Low Illumination 1.3 MP HD Colorful Camera		
	Video compression standard	H.264		
	Resolution	1280 × 720		
	Video frame rate	25 fps		
Audio parameters	Audio input	Built-in Omnidirectional Microphone		
	Audio output	Built-in Loudspeaker		
	Audio compression standard	G.711 U		
	Audio compression rate	64 Kbps		
	Audio quality	Noise Suppression and Echo Cancellation		
Access control parameters	Internal card reader	Built-in IC Card Reader		
	Exit button	Exit Button for Opening the Door		
	Door magnetic detection	Detects Door Magnetic Status		
Light supplement	Light supplement mode	IR Supplement		
Network parameters	Ethernet	10/100 Mbps Self-Adaptive Ethernet		
	Network protocol	TCP/IP, RTSP		
Alarm parameters	Alarm input	Door Magnetic Alarm, Tampering Alarm		
Device interfaces	Network interface	1 RJ-45 10/100 Mbps Self-Adaptive Ethernet Interface		
	RS-485	1 RS-485 Half-Duplex Port		
	I/O input	4		
	I/O output	1		
General	Indoor station access amount	1	2	4
	Material	Aluminum Alloy		
	Power supply	24 VDC, Power Over Network Cable (DS-KAD606, DS-KAD612)		
		12 VDC		
	Power consumption	≤12 W		
	Working temperature	-40° C to +60° C (-40° F to 140° F)		
	Working humidity	10% to 90%		
	IP protection level	IP65		
	Dimensions (L × W × H)	182 mm × 100 mm × 33 mm (7.17" × 3.94" × 1.30")		
Certification	FCC, IC, CE, C-TICK, ROHS, REACH, WEEE			