

## Specifications

Model		DS-WSEWI-T2	DS-WSEWI-T4
System	Processor	Intel® Celeron® Processor J3455 (2M Cache, up to 2.3 GHz), 64 bit, 4 Core;	
	Memory	DDR3L, 4GB	
	Graphics card	Intel® HD Graphics 500	
	Operating system	Win10 IoT Ent LTSB 2016 Entry EPKEA, 64 bit	
Storage	System disk (OS, VMS)	mSATA 64GB	
		<b>Optional:</b> mSATA 128GB	
	SATA interface	2 SATA interfaces	4 SATA interfaces
		1TB/2TB/3TB/4TB/5TB/6TB/8TB/10TB capacity for each disk	
Video/Audio output	HDMI interface	2 ×HDMI interface	
		4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	
	VGA interface	1 × VGA interface	
		1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	
	Audio input	1-ch, 3.5 mm audio connector	
Audio output	1-ch, 3.5 mm audio connector		
External interface	LAN	2 × RJ45 10M/100M/1000M self-adaptive Ethernet interface	
	USB interface	Front panel: 2 × USB 2.0; Rear panel: 4 × USB 3.0	
	Serial interface	RS-232; RS-485	
	Alarm input / output	4/2	16/4
General	Power supply	100 to 240 VAC, 50 to 60 Hz	
	Consumption (without hard disk)	≤ 30 W	
	Working temperature	0 to +45° C (+32 to +113° F)	
	Working humidity	10 to 90 % (Non-condensing)	
	Chassis	19-inch rack-mounted 1U chassis	19-inch rack-mounted 1.5U chassis
	Dimensions (W × D × H)	445 × 290 × 45 mm (17.5" × 11.4" × 1.8")	445 × 400 × 71 mm ( 17.5"× 15.7" × 2.8")
	Weight (without hard disk)	≤ 3 kg (6.6 lb)	≤ 5 kg (11 lb)