

Specifications

Model		DS-WSPWI-T8
System	Processor	Intel® Xeon® Processor E3-1225 v5, 3.30 GHz
		Optional: <ul style="list-style-type: none"> ● G4400 3M Cache,3.30GHz; ● i3-6100 3M Cache,3.70GHz; ● i5-6500 6M Cache,3.20GHz; ● i7-6700 8M Cache,3.40GHz
	Memory	2 Memory Slots, 2 x 4 GB
		Optional: 4 x 8 GB
	Graphics card	Intel® HD Graphics
	PCIe slot	1 PCIe x16
Operating system	Win10 IoT Ent LTSB 2016 Entry EPKEA, 64 bit	
Storage	System disk (OS, VMS)	mSATA 64GB
		Optional: mSATA 128GB
	SATA interface	8 SATA interfaces
		1TB/2TB/3TB/4TB/5TB/6TB/8TB/10TB capacity for each disk
RAID card	Optional	
TPM encryption board	Optional	
Video/Audio output	HDMI interface	2 × HDMI interface
		4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
	VGA interface	1 × VGA interface
		1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Audio input	1-ch, 3.5 mm audio connector	
Audio output	1-ch, 3.5 mm audio connector	
External interface	LAN	2 × RJ45 10M/100M/1000M self-adaptive Ethernet interface
		Optional: 4 × RJ45 10M/100M/1000M self-adaptive Ethernet interface
	USB interface	Front panel: 2 × USB 2.0; Rear panel: 4 × USB 3.0
	Serial interface	RS-232; RS-485
Alarm Input / Output	Optional: 16/4	
General	Power supply	100 to 240 VAC, 50 to 60 Hz
	Consumption (without hard disk)	≤ 30 W
	Working temperature	0 to +45° C (+32 to +113° F)
	Working humidity	10 to 90 % (Non-condensing)
	Chassis	19-inch rack-mounted 2U chassis
	Dimensions (W × D × H)	445 × 470 × 90 mm (17.5"× 18.5" × 3.5")
	Weight (without hard disk)	≤ 8 kg (17.6 lb)