

U/UTP 4Pairs CCA cable-category6-PVC Sheath

Content of the Data Sheet

Sheath Printing	HIKVISION U/UTP 4PR CAT6 CCA PVC xxxxm mm/dd/yyyy Tracing Code-HS				
Model	DS-1LN6U-W/CCA				
Category	CAT. 6 CCA U/UTP 4x2x23AWG/1 PVC				
Conductor	Material	CCA (Copper content: 27%)			
	Nom.O.D.(mm)	0.585	up	+0.01	
			down	-0.01	
Insulation	Material	Solid HDPE			
	Diameter	1.05±0.05mm			
Sheath	Thickness	0.50±0.05 mm			
	External O.D.	6.0±0.30 mm			
	Surface	Clean, Frap, Satiation			
	Material	FR-PVC(complies RoHS)			
	Color	White RAL9003			
Surface Printing	Letter height	2.5±0.2mm			
	Color	Black			
	Print error & Space	≤±0.5%, 1m			
Core Color	1 Blue & White/ Blue		2 Orange & White/ Orange		
	3 Green & White/ Green		4 Brown & White/ Brown		
Packing	Carton				
Carton dimension	41x41x24cm				
Packing length	(305±1.5)m				
Rip-cord	Yes	Drain wire	No		
Sheath Physical Properties	Before Aging	Tensile Strength (Mpa)	≥13.5		
		Elongation(%)	≥150		
	Aging Period(°Cxhrs)	100°Cx24hx7d			
	After Aging	Tensile Strength(Mpa)	≥12.5, variance ratio: ±25%		
		Elongation(%)	≥125, variance ratio: ±20%		
	Cold bend(-20±2°Cx4h)	8xCable O.D., No visible cracks			
Electrical Characteristics (20°C)	1.0-100.0MHz	Impedance(Ω)	100±15		
	100 - 250MHz	Impedance(Ω)	100±25		
	1.0-100.0MHz	Delay Shew (ns/100m)	≤45		
		DC ResistanceΩ/100m) max	12		
		DC Conductor Resistance Unbalance(%) max	2		

Technical Performance(90m Fluke Link test):					
	Frequency (MHz)	RL	ATT	NEXT	Phase DELAY
		Min. dB	Max. dB/100m	Min. dB	Max. ns/100m
	4	23.0	3.8	66.3	552
	8	24.5	5.3	61.8	547
	10	25.0	6.0	60.3	545
	16	25.0	7.6	57.2	543
	20	25.0	8.5	55.8	542
	25	24.3	9.5	54.3	541
	31.25	23.6	10.7	52.9	540
	62.5	21.5	15.4	48.4	539
	100	20.1	19.8	45.3	538
	200	18.0	29.0	40.8	537
	250	17.3	32.8	39.3	536
	Frequency (MHz)	PSNEXT	ELFEXT	PSELFEXT	
		Min. dB	Min. dB	Min. dB	
	4	63.3	56.0	53.0	
	8	58.8	49.9	46.9	
	10	57.3	48.0	45.0	
	16	54.2	43.9	40.9	
	20	52.8	42.0	39.0	
	25	51.3	40.0	37.0	
	31.25	49.9	38.1	35.1	
	62.5	45.4	32.1	29.1	
	100	42.3	28.0	25.0	
	200	37.8	22.0	19.0	
	250	36.3	20.0	17.0	

Ambient temperature: -20°C - 70°C