

## Specification

Model	DS-1LN6U-G	
Category	Cat.6	
Sheath printing	HIKVISION 4PR 23AWG 75°C U/UTP CAT6 VERIFIED TO ANSI/TIA-568-C.2 PVC ****m mm/dd/yyyy Tracing Code-HS	
Reference standard	ISO/IEC11801, ANSI/TIA-568-C.2, RoHS 2.0	
Fire resistance	No	
Conductor	Material	Solid-Bare Copper (99.95%)
	Diameter	0.55 ± 0.005 mm, 23 AWG
Insulation	Material	HDPE
	Diameter	0.98 ± 0.05 mm
Sheath	Thickness	0.50 ± 0.10 mm
	Diameter	6.00 ± 0.30 mm
	Material	PVC
	Color	Grey
Rip-cord	Yes	
Separator	Yes	
Sheath physical properties	Before aging	Tensile strength ≥ 13.5 Mpa Elongation ≥ 150%
	Aging period	100°C × 24h × 10d
	After aging	Tensile strength ≥ 12.5 Mpa Elongation ≥ 125%
	Cold bend	-20 ± 2°C × 4h, 8 × cable O.D, no visible cracks
Electrical Characteristics (20°C)	1.0-250.0 MHz impedance	100 ± 15 Ω @ ≤ 100 MHz
		100 ± 25 Ω @ 100-250 MHz
	1.0-250.0 MHz delay skew	≤ 45 ns/100 m
	DC resistance	≤ 9.38 Ω/100 m
	DC conductor resistance unbalance	≤ 5.0%
	Package dimension	400 mm (W) × 400 mm (H) × 240 mm (D) (15.75" × 15.75" × 9.45")
	Weight	12.3 ± 0.5kg
	Cable length	(305 ± 1.5) m
Ambient temperature	-20°C to 75°C (-4°F to 167°F)	
Operating voltage	60 V	