

- Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out
- Supports multiple languages: English, Spanish, and Arabic
- * **Biometric recognition products are not 100% applicable to anti-spoofing environments. If you require a higher security level, use multiple authentication modes**

Specifications

| Model | DS-K1T331 | DS-K1T331W |
|--|---|---------------|
| Operating system | Linux | |
| Screen | 3.97-inch touch screen | |
| Card capacity (when connecting external card reader) | 1,500 | |
| Event capacity | 150,000 | |
| Face capacity | 300 | |
| Face recognition distance | 0.3 m to 1.5 m | |
| Face recognition duration | < 0.2 s | |
| Network interface | 10/100 Mbps, self-adaptive | |
| Camera | 2 MP dual-lens camera with wide dynamic range | |
| Communication | TCP/IP | TCP/IP, Wi-Fi |
| Interface | USB × 1, electric lock × 1, door contact × 1, tamper × 1, exit button × 1, RS-485 × 1 | |
| Power supply | 12 V, 1.5 A, 18 W | |
| Working humidity | 10 to 90% (no condensing) | |
| Working temperature | -10 °C to +50 °C (14 °F to +122 °F) | |
| Application environment | Indoor use | |
| Dimension (W × H × D) | 120 mm × 110 mm × 23 mm (4.7" × 4.3" × 0.9") | |

* *Exposing the equipment to direct sun light, low ventilation or heat source such as heater or radiator is forbidden (ignorance can cause fire danger).*