

SM-LED22A-2K 22" Professional LED Monitor



Key Features:

1. HD: 1920*1080, 4 times higher than normal monitor.
2. Turn on the screen to automatically detect the resolution of the input signal in the upper right corner of the screen.
3. Clear: delicate and realistic, conveying true colors, showing the true colors.
4. Bright: The quality is improved, only for better presentation.
5. Adopt industrial screen, high brightness, high contrast.
6. High-precision standard regulated power supply, specially designed for industrial equipment, supporting 24 hours × 365 days of uninterrupted work.
7. Adopt 10bit image chip processing technology, high pixel progressive scan, fine texture.
8. Support intelligent 3D noise reduction, eliminate afterimage function, dynamic brightness, contrast color optimization technology.
9. Apply the world's leading LED driver solution to accurately restore the front-end signal, with a strong sense of reality.
10. LED has small volume, low energy consumption, zero radiation, stable image, no impact on the eyes, natural health.
11. 5 ms extremely fast response, avoiding the tailing phenomenon of images in high speed operation.
12. Using nanotechnology, the picture is more three-dimensional, transparent.

Specification

Product type	Professional Monitor
Product model	SM-LED22A-2K
Screen size	22"
Screen type	LED
Screen ratio	16:9
Brightness	450nit
Contrast ratio	3000:1
Response time	5 ms
Visual area	478*278
Viewing angle	160°/ 170°
Display color	16.7M

Clearness	1920*1080
Control method	panel infrared
Input port	HDMI,VGA
Audio output	2 stereo speakers
Power supply mode	220V / 0.7A
Power frequency	50/Hz
Total power	50W
Case	fireproof plastic
Product outer dimensions	510*315 does not include foot height (foot height 25mm)
Installation method	base, wall mount (with 4 * Hexagonal column screw)
Product weight	2.4kg
Packing	(1pcs) 550*430*105 /3.3kg; (5pcs) 560*440*540/17.5kg
Working environment temperature	most suitable for 20
Working environment humidity	10%-90% RH
Storage temperature	- 20^∘C~ 60^∘C

