













## **Product Features**

- 1080P FHD resolution, the image is more clear and delicate;
- Captures moving images without aliasing with 2 million progressive scan CMOS
- Support AHD/TVI/CVI coaxial HD output, clear and delicate images
- Illumination, 0.01Lux@(F1.2, AGC ON), 0LUX with IR
- Support Warm Light
- Support OSD menu control, suitable for user-defined settings
- Support for digital wide dynamics
- Adaptive digital noise reduction, 3D-DNR, 2D-DNR
  Support for coaxial view control (UTC)
- Video 6KV lightning protection, power supply large capacitor
- design Support DC 12V1-2A wide voltage supply













	Model	SM-PR6322-FC
Camera Features	Image sensor	1/2.7" 2MP CMOS Sensor
	Video output	1080P@25fps / 1080P@30fps
	PAL/NTSC	TV System
	Signal format	AHD/TVI/CVI/CVBS
	Min. Illumination	0.01Lux@(F1.2,AGC ON), OLUX with IR
	Shutter	1/50(1/60) seconds to 1/100,000 seconds
	Day/Night	Color/ B&W (IR-CUT)
Lens	Focus Length	2.8mm/F2.0
	Pixels	2MP (1920x1080)
Night Vision	Warm LED	4PCS Warm Light
	WarmLight Distance IR	20M
	IR Status	-
	IR Power On	-
General General	Material	Plastic waterproof
	UTC	Support
	Protect Grade	IP67
	OSD	Optional
	Language	English, Chinese Simplified, Chinese Traditional, Bulgarian,etc
	- Operation	-10°C- + 60°C
	Temperature Storage	10%-90% RH
	Temperature Power	DC12V±10%
	Supply Consumption	MAX 12W
	Dimensions	160(W) x62(H) x 62(D)mm
	Weight	About 500g









